

BULLDOG Hybrid Performance Data (English (I-P) Units) - 3 gpm/ton

Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow (GPM)	Water Loop Heat Pump		
		Cooling	Heating		Cooling 86F EWT		Heating 120F EWT
				Capacity (BTU/h)	EER	Capacity (BTU/h)	
SKH008	R-454B	240	240	2.0	10270	15.9	13196
SKH010	R-454B	300	300	2.5	10378	14.9	14853
SKH012	R-454B	400	400	3.0	12739	16.1	17529
SKH015	R-454B	500	500	3.8	15018	15.0	20747
SKH018	R-454B	600	600	4.5	18254	13.4	23676
SKH020	R-454B	700	700	5.0	20738	18.4	31460
SKH024	R-454B	800	800	6.0	25398	17.4	34882
SKH030	R-454B	1000	1000	7.5	29964	16.5	41712
SKH036	R-454B	1200	1200	9.0	35205	15.6	46977
SKH042	R-454B	1400	1400	10.5	43065	17.1	57701
SKH048	R-454B	1600	1600	12.0	50862	16.0	63628
SKH060	R-454B	2000	2000	15.0	60185	14.6	74471
SKH070	R-454B	2400	2400	17.5	76540	16.1	103950
SKH080	R-454B	2800	2800	20.0	85623	15.7	116595
SKH100	R-454B	3200	3200	25.0	103850	15.1	130904

Cooling capacities based upon 80.6F DB, 66.2F WB entering air temperature.

Heating capacities based upon 68F DB, 59F WB entering air temperature.

All units AHRI/ASHRAE 13256-1 rated on high speed motor TAP.

All ratings based upon operation at lower voltage models.

BULLDOG Hybrid Performance Data (English (I-P) Units) - 2 gpm/ton

Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow (GPM)	Water Loop Heat Pump		
		Cooling	Heating		Cooling 86F EWT		Heating 120F EWT
				Capacity (BTU/h)	EER	Capacity (BTU/h)	
SKH008	R-454B	240	240	1.4	9916	14.7	11924
SKH010	R-454B	300	300	1.7	10079	14.1	13421
SKH012	R-454B	400	400	2.0	12368	15.2	15839
SKH015	R-454B	500	500	2.5	14602	14.3	18747
SKH018	R-454B	600	600	3.0	17718	12.8	21394
SKH020	R-454B	700	700	3.5	20221	17.8	28427
SKH024	R-454B	800	800	4.0	24718	16.8	31519
SKH030	R-454B	1000	1000	5.0	29114	16.3	37246
SKH036	R-454B	1200	1200	6.0	34277	15.2	42449
SKH042	R-454B	1400	1400	7.0	41762	16.5	52138
SKH048	R-454B	1600	1600	8.0	49357	15.5	57494
SKH060	R-454B	2000	2000	10.0	58470	14.4	67292
SKH070	R-454B	2400	2400	12.0	75401	15.6	93930
SKH080	R-454B	2800	2800	14.0	84156	15.1	105357
SKH100	R-454B	3200	3200	16.0	102490	14.3	118195

Cooling capacities based upon 80.6F DB, 66.2F WB entering air temperature.

Heating capacities based upon 68F DB, 59F WB entering air temperature.

All units AHRI/ASHRAE 13256-1 rated on high speed motor TAP.

All ratings based upon operation at lower voltage models.