

### BULLDOG Reversing Performance Data (English (I-P) Units) - 3 gpm/ton

Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow	Water Loop Heat Pump			
		Cooling	Heating	(GPM)	Cooling 86F EWT		Heating 68F EWT	
					Capacity (BTU/h)	EER	Capacity (BTU/h)	COP
SRH008	R-454B	240	240	2.0	10213	15.8	12573	4.5
SRH010	R-454B	300	300	2.5	10547	16.4	13364	5.4
SRH012	R-454B	400	400	3.0	12715	16.0	16239	5.4
SRH015	R-454B	500	500	3.8	15247	15.2	19990	5.4
SRH018	R-454B	600	600	4.5	18254	13.4	25099	5.0
SRH020	R-454B	700	700	5.0	20811	17.5	25520	6.4
SRH024	R-454B	800	800	6.0	25398	17.3	31826	5.7
SRH030	R-454B	1000	1000	7.5	29531	16.7	38372	6.1
SRH036	R-454B	1200	1200	9.0	34565	15.1	46913	5.8
SRH042	R-454B	1400	1400	10.5	42837	16.7	55039	6.0
SRH048	R-454B	1600	1600	12.0	50817	16.2	66520	5.7
SRH060	R-454B	2000	2000	15.0	62129	14.5	85782	5.4
SRH070	R-454B	2400	2400	17.5	76540	16.1	91368	5.2
SRH080	R-454B	2800	2800	20.0	85623	15.7	101172	5.5
SRH100	R-454B	3200	3200	25.0	103850	15.1	117824	5.0

Cooling capacities based upon 80.6F DB, 66.2F WB entering air temperature.

Heating capacities based upon 68F DB, 59F WB entering air temperature.

All units AHRI/ASHRAE 13256-1 rated on high speed motor TAP.

All ratings based upon operation at lower voltage models.

### BULLDOG Reversing Performance Data (English (I-P) Units) - 2 gpm/ton

Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow	Water Loop Heat Pump			
		Cooling	Heating	(GPM)	Cooling 86F EWT		Heating 68F EWT	
					Capacity (BTU/h)	EER	Capacity (BTU/h)	COP
SRH008	R-454B	240	240	1.4	9863	14.4	12008	4.5
SRH010	R-454B	300	300	1.7	10248	15.2	12755	5.2
SRH012	R-454B	400	400	2.0	12346	14.9	15470	5.3
SRH015	R-454B	500	500	2.5	14818	14.2	19058	5.2
SRH018	R-454B	600	600	3.0	17718	12.6	23930	4.8
SRH020	R-454B	700	700	3.5	20313	17.6	24408	6.1
SRH024	R-454B	800	800	4.0	24493	16.6	30072	5.4
SRH030	R-454B	1000	1000	5.0	28702	15.9	36571	5.8
SRH036	R-454B	1200	1200	6.0	33665	14.6	44740	5.6
SRH042	R-454B	1400	1400	7.0	41638	15.9	52571	5.8
SRH048	R-454B	1600	1600	8.0	49312	15.2	63370	5.5
SRH060	R-454B	2000	2000	10.0	60508	13.9	81390	5.2
SRH070	R-454B	2400	2400	12.0	75401	15.6	87399	5.0
SRH080	R-454B	2800	2800	14.0	84156	15.1	96882	5.3
SRH100	R-454B	3200	3200	16.0	102490	14.3	113318	4.9

Cooling capacities based upon 80.6F DB, 66.2F WB entering air temperature.

Heating capacities based upon 68F DB, 59F WB entering air temperature.

All units AHRI/ASHRAE 13256-1 rated on high speed motor TAP.

All ratings based upon operation at lower voltage models.