

INNKEEPER/HOMEKEEPER Vertical Stacked

BULLDOG HYBRID Performance Data (English (I-P) Units) - 2 gpm/ton							
Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow (GPM)	Water Loop Heat Pump		
		Cooling	Heating		Cooling 86F EWT*		Heating 120F EWT**
				Capacity (BTU/h)	EER	Capacity (BTU/h)	
IKV008	R-454B	240	240	1.4	10002	14.5	10504
IKV010	R-454B	300	300	1.7	10358	14.7	12672
IKV012	R-454B	360	360	2.0	11827	14.8	14535
IKV015	R-454B	450	450	2.5	14191	14.6	17148
IKV018	R-454B	540	540	3.0	17087	13.3	19504
HKV016	R-454B	500	500	3.5	15585	16.6	19266
HKV020	R-454B	600	600	4.0	18896	15.6	22239
HKV024	R-454B	720	720	5.0	24270	14.3	25500
HKV030	R-454B	900	900	6.0	27590	13.9	29855
HKV036	R-454B	1080	1080	7.0	37428	15.8	42061
HKV042	R-454B	1260	1260	8.0	43123	16.1	47188
HKV048	R-454B	1440	1440	10.0	49289	15.3	51988

*Cooling performance shown based on 80.6F DB and 66.2F WB entering air

**Heating performance shown based on 68F entering air

Rated in accordance with ANSI/AHRI/ASHRAE/ISO Standard 13256-1

