

### SPACEKEEPER - Vertical Floor Mounted

BULLDOG HYBRID Performance Data (English (I-P) Units) - 2 gpm/ton							
Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow	Water Loop Heat Pump		
		Cooling	Heating		Cooling 86F EWT*		Heating 120F EWT**
				Capacity (BTU/h)	EER	Capacity (BTU/h)	
SKV008	R-454B	240	240	1.4	10130	13.8	10987
SKV010	R-454B	320	320	1.7	10637	14.4	13795
SKV012	R-454B	400	400	2.0	12755	13.7	16342
SKV015	R-454B	500	500	2.5	15162	12.9	19411
SKV018	R-454B	600	600	3.0	16710	12.2	22222
SKV020	R-454B	700	700	3.5	19405	14.3	26720
SKV024	R-454B	800	800	4.0	23953	13.7	29900
SKV030	R-454B	1000	1000	5.0	28954	13.6	35144
SKV036	R-454B	1200	1200	6.0	33336	13.2	39872
SKV042	R-454B	1400	1400	7.0	43807	13.9	53336
SKV048	R-454B	1600	1600	8.0	50799	13.6	58928
SKV060	R-454B	2000	2000	10.0	58135	13.3	69204
SKV070	R-454B	2400	2400	18.0	67667	13.1	92316
SKV080	R-454B	2800	2800	21.0	84364	16.1	103018
SKV100	R-454B	3200	3200	24.0	99261	14.8	115772

\*Cooling performance shown based on 80.6F DB and 66.2F WB entering air

\*\*Heating performance shown based on 68F entering air

Rated in accordance with ANSI/AHRI/ASHRAE/ISO Standard 13256-1

