

### SPACEKEEPER - Horizontal Ceiling Mounted

BULLDOG REVERSING Performance Data (English (I-P) Units) - 3 gpm/ton								
Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow (GPM)	Water Loop Heat Pump			
		Cooling	Heating		Cooling 86F EWT*		Heating 68F EWT**	
				Capacity (BTU/h)	EER	Capacity (BTU/h)	COP	
SRH008	R-454B	240	240	2.0	7602	16.0	9970	5.5
SRH010	R-454B	320	320	2.5	10706	16.3	13138	5.3
SRH012	R-454B	400	400	3.0	13024	16.2	15878	5.2
SRH015	R-454B	500	500	3.8	15594	15.0	19441	5.0
SRH018	R-454B	600	600	4.5	18714	13.4	24272	4.6
SRH020	R-454B	700	700	5.3	20854	17.9	25218	6.3
SRH024	R-454B	800	800	6.0	25175	16.6	31334	5.7
SRH030	R-454B	1000	1000	7.5	30995	15.6	38969	5.3
SRH036	R-454B	1200	1200	9.0	37548	14.9	48852	5.2
SRH042	R-454B	1400	1400	10.5	41936	15.8	53907	5.8
SRH048	R-454B	1600	1600	12.0	51213	15.5	65511	5.4
SRH060	R-454B	2000	2000	15.0	61965	14.0	84232	5.1
SRH070	R-454B	2400	2400	18.0	78000	17.6	94947	5.5
SRH080	R-454B	2800	2800	21.0	85514	17.3	105558	5.6
SRH100	R-454B	3200	3200	24.0	100699	16.1	129027	5.3

\*Cooling performance shown based on 80.6F DB and 66.2F WB entering air

\*\*Heating performance shown based on 68F entering air

Rated in accordance with ANSI/AHRI/ASHRAE/ISO Standard 13256-1

