

SPACEKEEPER - Vertical Floor Mounted

BULLDOG REVERSING Performance Data (English (I-P) Units) - 3 gpm/ton								
Model with ECM Motor	Refrigerant	Airflow (SCFM)		Water Flow (GPM)	Water Loop Heat Pump			
		Cooling	Heating		Cooling 86F EWT*		Heating 68F EWT**	
				Capacity (BTU/h)	EER	Capacity (BTU/h)	COP	
SRV008	R-454B	240	240	2.0	7675	16.2	10027	5.3
SRV010	R-454B	320	320	2.5	10786	16.5	13287	5.2
SRV012	R-454B	400	400	3.0	13048	16.3	16151	5.3
SRV015	R-454B	500	500	3.8	15682	15.2	19884	5.2
SRV018	R-454B	600	600	4.5	18893	13.6	24962	4.9
SRV020	R-454B	700	700	5.3	19698	16.8	25595	6.1
SRV024	R-454B	800	800	6.0	24254	16.0	31845	5.7
SRV030	R-454B	1000	1000	7.5	30595	15.3	39871	5.5
SRV036	R-454B	1200	1200	9.0	36581	14.5	49555	5.1
SRV042	R-454B	1400	1400	10.5	42715	16.1	54896	5.9
SRV048	R-454B	1600	1600	12.0	51773	15.7	66665	5.5
SRV060	R-454B	2000	2000	15.0	62664	14.1	85715	5.1
SRV070	R-454B	2400	2400	18.0	62664	14.1	85715	5.1
SRV080	R-454B	2800	2800	21.0	84482	17.0	105757	5.6
SRV100	R-454B	3200	3200	24.0	100336	16.1	129023	5.3

*Cooling performance shown based on 80.6F DB and 66.2F WB entering air

**Heating performance shown based on 68F entering air

Rated in accordance with ANSI/AHRI/ASHRAE/ISO Standard 13256-1

