

Rated in accordance with ASHRAE/AHRI/ISO 13256-1

| | | Model | Water Loop Heat Pump | |
|--|-------------------------------------|--------|----------------------|--------------|
| | | | Cooling EWT 86°F | |
| | | | Capacity (Btuh) | EER (Btuh/W) |
| SpaceKeeper Verticals (SKV & SEV) | Standard | SKV008 | 8,601 | 15.10 |
| | | SKV010 | 9,532 | 14.30 |
| | | SKV012 | 12,190 | 14.10 |
| | | SKV015 | 14,438 | 14.00 |
| | | SKV018 | 17,108 | 13.80 |
| | | SKV020 | 18,850 | 15.60 |
| | | SKV024 | 23,089 | 16.00 |
| | | SKV030 | 26,241 | 13.70 |
| | | SKV036 | 30,112 | 13.30 |
| | | SKV042 | 41,125 | 16.30 |
| | | SKV048 | 49,842 | 16.60 |
| | | SKV060 | 55,403 | 14.30 |
| | | SKV070 | 71,041 | 15.10 |
| | | SKV080 | 80,691 | 14.20 |
| | High Efficiency E-Series | SEV008 | 9,274 | 16.50 |
| | | SEV010 | 10,318 | 15.50 |
| | | SEV012 | 12,925 | 15.20 |
| | | SEV015 | 15,285 | 15.30 |
| | | SEV018 | 18,294 | 17.20 |
| | | SEV020 | 19,274 | 18.30 |
| | | SEV024 | 24,602 | 18.10 |
| | | SEV030 | 30,009 | 18.50 |
| | | SEV036 | 38,591 | 18.40 |
| | | SEV042 | 42,199 | 17.40 |
| SEV048 | 54,045 | 18.60 | | |
| SEV060 | 61,225 | 16.50 | | |
| SEV070 | 74,891 | 16.60 | | |

Cooling Capacities based upon 80.6°F (27°C) DB, 66.2°F (19°C) WB entering air temperature, EWT of 86°F (30°C)

* Fan motors are EC type