



- Note:**
- \* Door may be hinged on either side. However, a minimum of 4" must be allowed on hinged side for proper unit access.
  - \* Plenum height addition "x" available in 2 inch increment to a limit of 46" in total plenum height
  - \* Water connections to unit to be completed by third party
  - \* Following standard filters are included:
    - \* Chassis : (2) 16" x 20" 2" MERV7 filter
    - \*ERV : 14" x 16.75" wire frame RA filter + 16" x 22" wire frame FA filter
  - \* 3' Supply / return hoses (3/4") included.

<p>PROPRIETARY AND CONFIDENTIAL</p>	<p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CGC Group. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CGC Group IS PROHIBITED.</p>	NAME:	DATE (MM/DD/YYYY):	TITLE:
		DRAWN: DI	2020-06-02	KlassKeeper with exposed cabinet and air plenum
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES		CHECKED:		MODEL:
TOLERANCES UNLESS OTHERWISE NOTED ARE:		MATERIAL:		KKV 024-048
<p>FRACTIONAL ± 1/16"</p> <p>ANGULAR ± 0.5°</p> <p>X ± .1"</p> <p>.XX ± .06"</p> <p>.XXX ± .032"</p> <p>.XXXX ± .0050"</p>		FINISH:		SIZE DWG. NO. REV.:
				B A
				SCALE: NTS WEIGHT: lbs SHEET 1 OF 1